



# *SuperSeal*<sup>TM</sup> Sealing Agent

*SuperSeal*<sup>TM</sup> was developed as an economical, fast-drying sealing agent for a variety of porous surfaces including gypsum plasters, concrete and wood. This sealing agent will quickly and effectively seal surfaces without interfering with surface detail. The new formula offers better performance and faster evaporation. Mold rubber (polyurethane, silicone or polysulfide) can then be applied.

## Advantages Of Using *SuperSeal*<sup>TM</sup>

- **Low Cost**
- **Low Viscosity** - wets out well over any surface.
- **Evaporates Quickly**
- **Ultra Thin Film** - does not interfere with reproduction of surface detail or finish. Gives cured rubber mold surface a smooth, satin finish.
- **Removable** – can be rinsed from model surface with warm water.

## DIRECTIONS - Applying *SuperSeal*<sup>TM</sup> Sealing Agent

CONTENTS FLAMMABLE. Keep product away from flame and all ignition sources. Store and use at room temperature. This product has a limited shelf life. . . use as soon as possible. Good ventilation (room size) is essential. Wear safety glasses, long sleeves and rubber gloves to minimize contamination risk.

### NOTE: ALWAYS SHAKE WELL BEFORE USING

A minimum of 2 coats of *SuperSeal*<sup>TM</sup> is recommended to seal most surfaces. For extremely porous surfaces (i.e. limestone or dry plaster) an additional coat of *SuperSeal*<sup>TM</sup> may be required. Or apply two coats of *SuperSeal*<sup>TM</sup> and follow with an application of Ease Release 200.

*SuperSeal*<sup>TM</sup> can be applied using a soft brush or a non-aerosol spray bottle to lightly mist *SuperSeal*<sup>TM</sup> onto model.

1. Apply a thorough thin coating of *SuperSeal*<sup>TM</sup> over entire model surface and surrounding forms including intricate detail and undercuts. Compressed air or a hair dryer may be used to blow off any excess that has pooled. Let dry for 5 minutes.
3. Repeat above 1 - 2 more times and let final coat dry for at least 1 hour.

*(Continued on Reverse Side)*

4. If recommended by mold rubber manufacturer, apply a light mist coating of release agent (i.e. Ease Release 200).

**Because no two applications are quite the same, a small test application to determine suitability for your project is recommended if performance of this material is in question.**

**Important:** Discoloration of model surface may occur. If compatibility between *SuperSeal*<sup>™</sup> and model surface or *SuperSeal*<sup>™</sup> and a particular mold rubber is a concern, a small-scale test should be made on an identical surface prior to use.

### ***SAFETY FIRST***

The material safety data sheet (MSDS) for this or any other Smooth-On product should be read prior to use and is available upon request from Smooth-On. All Smooth-On products are safe to use if directions are read and followed carefully.

**Be careful.** CONTENTS FLAMMABLE. Keep product away from heat, sparks, or open flame. Do not puncture, or incinerate container. Do not expose to heat or store at temperatures above 120F/48C. Use only with adequate ventilation. Contains Naphtha CAS# 64742-48-9

**DANGER: HARMFUL OR FATAL IF SWALLOWED. FLAMMABLE. EYE IRRITANT.**

Contains Petroleum Distillates and Isopropanol. Keep away from heat, sparks and open flames. Avoid contact with eyes and prolonged contact with skin.

Do not ingest.

**First Aid:** In case of eye contact, flush with water for 15 minutes. If irritation persists, get medical attention. If swallowed, do not induce vomiting. Call physician immediately.

**Keep Out Of Reach Of Children.**

Important: The information contained in this bulletin is considered accurate. However, no warranty is expressed or implied regarding the accuracy of the data, the results to be obtained from the use thereof, or that any such use will not infringe upon a patent. User shall determine the suitability of the product for the intended application and assume all risk and liability whatsoever in connection therewith.

***Toll-Free Technical Help: (800) 762-0744***

**Fax: (610) 252-6200 \* Web: [smooth-on.com](http://smooth-on.com)**